

## Specification Sheet

Part Number: 157-00332



All-in-one bundling and fastening solution reduces costs and assembly time.  
Anti-rotational oval fastener forces bundle to travel in intended direction.  
High-spec materials and superior design deliver excellent performance and value.

1-Pc Cable Tie/Fir Tree Mount with Disc, 9"L, 6.2 - 13.0 mm, PA46, Brown, 1000/bag

<b>Article Number</b>	157-00332
<b>Type</b>	T50ROSFTOVAL25B
<b>Color</b>	Brown (BN)
<b>Quantity Per</b>	bag
<b>Product Description</b>	One-piece cable tie and mount offers a simple bundling and mounting solution. The innovative design of this fir tree establishes a 360-degree interface with the panel hole, ensuring a more secure fit. The oval shape won't rotate once inserted, ensuring proper routing of wires and hoses. The disc feature prevents rattling in high-vibration applications and protects against debris ingress.
<b>Short Description</b>	1-Pc Cable Tie/Fir Tree Mount with Disc, 9"L, 6.2 - 13.0 mm, PA46, Brown, 1000/bag

**Global Part Name**

T50ROSFTOVAL25B-PA46-BN

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225.0

**Length L (Imperial)**

9.0

**Length L (Metric)**

229.3

**Offset Length (Imperial)**

0.98

**Offset Length (Metric)**

25.0

**Fixation Method**

Fir Tree for oval holes

**Identification Plate Position**

none

**Releasable Closure**

No

**Variant**

Outside Serrated

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.70

**Bundle Diameter Min (Imperial)**

0.08

**Bundle Diameter Min (Metric)**

2.0

**Bundle Diameter Max (Imperial)**

1.97

<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.27
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.51 " 0.27 x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.51
<b>Mounting Hole Diameter D Max (Metric)</b>	13.0
<b>Disc Diameter (Metric)</b>	17.63 x 23.63
<b>Disc Diameter (Imperial)</b>	0.69 x 0.93

**Material** Polyamide 4.6 (PA46)

**Material Shortcut** PA46

**Flammability** UL 94 V2

**Operating Temperature** -40°F to +266°F (-40°C to +130°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000