

Specification Sheet

Part Number: 157-00335



Offset Low-Profile Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg

Article Number	157-00335
Type	T50ROSLPM6SMS025
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Offset design positions bundles away from obstructions, heat or sources of abrasion.• Low profile head allows mounts to stack, providing more mounting versatility from a single stud.• Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.• PA46 material option allows use in high-heat applications..
Quantity Per	carton

Product Description

This mount's offset design positions bundles away from obstructions, heat or sources of abrasion. It features a low-profile head, allowing multiple tie mounts to be stacked on a single bolt and providing space savings in tight areas. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description

Offset Low-Profile Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg

Global Part Name

T50ROSLPM6SMS025-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

223

Length L (Imperial)

8.8

Length L (Metric)

223.52

Offset Length(Imperial)

1.0

Offset Length(Metric)

25.5

Fixation Method

Stud Mount

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Width W (Imperial)

0.56

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Cable Ties 157-00335

Height H (Imperial) 0.25

Height H (Metric) 6.30

Mounting Hole Diameter D (Imperial) 0.24" x 0.04

Mounting Hole Diameter D (Metric) M6 x 1

Stud Diameter (Metric) 5.0 mm 6.0 mm

Stud Diameter (Imperial) 0.20 ", 0.24

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0026
Weight (Imperial)	0.006