

## Specification Sheet

Part Number: 157-00340



Low-profile head allows mounts to stack, providing more mounting versatility from a single stud.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

Low Profile M8 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA66HIRHS, Black, 2000/pkg

Article Number 157-00340

Type T80ROSLPSB8U

Color Black (BK)

Quantity Per carton

**Product Description**  
Mount features a low-profile head, allowing multiple tie mounts to be stacked on a single bolt and providing space savings in tight areas. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

**Short Description**  
Low Profile M8 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA66HIRHS, Black, 2000/pkg

Global Part Name T80ROSLPSB8U-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 80

Minimum Tensile Strength (Metric) 355

Length L (Imperial) 8.3

Length L (Metric) 212.0

Fixation Method Stud Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.70

Width W (Metric) 17.75

Bundle Diameter Min (Imperial) 0.14

Bundle Diameter Min (Metric) 3.5

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Cable Ties 157-00340

|                                     |  |
|-------------------------------------|--|
| Height H (Imperial)                 | 0.25   |
| Height H (Metric)                   | 6.30   |
| Mounting Hole Diameter D (Imperial) | 0.31 x 0.05  |
| Mounting Hole Diameter D (Metric)   | M8 x 1.25  |
| Stud Diameter (Metric)              | 8.0 mm   |
| Stud Diameter (Imperial)            | 0.31   |
| Material                            | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                   | PA66HIRHSUV  |
| Flammability                        | UL 94 HB   |
| Halogen Free                        | Yes  |
| UV Resistant (Yes/No)               | Yes  |
| Operating Temperature               | -40°F to +221°F (-40°C to +105°C)  |
| Reach Compliant (Article 33)        | Yes  |
| ROHS Compliant                      | Yes  |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 2000       |
| Package Quantity (Metric)   | 2000       |
| Customs Number              | 3926909988 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)