

Specification Sheet

Part Number: 157-00358



Standoff Fir Tree Cable Tie, 25mm standoff, 6.5mm Hole, 8" Tie, 50lb, PA66HIRHSUV, Black, 3000/ctn

| | |
|---------------------|---|
| Article Number | 157-00358 |
| Type | T50ROSFT1025SO |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• 1-Piece cable tie and fir tree mount offers a simple method to bundle and fasten cables to panels with thickness up to 6.0 mm.• Robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 10 mm hole.• 8 inch outside serrated tie with low profile head design provides security for bundles up to 50 mm.• 25 mm stand off on cable tie creates an alternate solution when an offset fastening option is required directly above the hole away from the mounting panel. |
| Quantity Per | carton |

Product Description

Offset Cable Ties route and position wire and cable bundles away from a mounting hole. The offset bar between the fir tree and cable tie strap provides a robust and cored-out design to eliminate any potential bending of the wire or cable assembly once installed. The combination of 12.5 mm and 25 mm offset distances and various fir tree sizes offer coverage for a majority of industry offset routing applications. The outside serrations of the tie strap prevent damage to soft or delicate bundles. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution.

Short Description

Standoff Fir Tree Cable Tie, 25mm standoff, 6.5mm Hole, 8" Tie, 50lb, PA66HIRHSUV, Black, 3000/ctn

Global Part Name

T50ROSFT1025SO-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

9.5

Length L (Metric)

242.3

Offset Length(Imperial)

0.98

Offset Length(Metric)

25.0

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.44

Width W (Metric)

11.3

Bundle Diameter Min (Imperial) 0.07

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.96

Bundle Diameter Max (Metric) 50.0

Mounting Hole Diameter D (Imperial) 0.39

Mounting Hole Diameter D (Metric) 10.0 mm

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Material Cable Tie Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3926909988

