

Specification Sheet

Part Number: 157-00362



Offset Low-Profile M8 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg

Article Number	157-00362
Type	T50ROSLPM8SMSO25
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Offset design positions bundles away from obstructions, heat or sources of abrasion.• Low profile head allows mounts to stack, providing more mounting versatility from a single stud.• Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.
Quantity Per	carton

Product Description

This mount's offset design positions bundles away from obstructions, heat or sources of abrasion. It features a low-profile head, allowing multiple tie mounts to be stacked on a single bolt and providing space savings in tight areas. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description	Offset Low-Profile M8 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg
Global Part Name	T50ROSLPM8SMSO25-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	223
Length L (Imperial)	8.9
Length L (Metric)	226.14
Offset Length(Imperial)	1.0
Offset Length(Metric)	25.5
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.70
Width W (Metric)	17.75
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0

Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Cable Ties	157-00362
Height H (Imperial)	0.25
Height H (Metric)	6.30
Mounting Hole Diameter D (Imperial)	0.31" x 0.05
Mounting Hole Diameter D (Metric)	M8 x 1.25
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes

Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0027
Weight (Imperial)	0.006