

Specification Sheet

Part Number: 157-00362



Offset Low-Profile M8 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg

Article Number	157-00362
Type	T50ROSLPM8SMS025
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Offset design positions bundles away from obstructions, heat or sources of abrasion.• Low profile head allows mounts to stack, providing more mounting versatility from a single stud.• Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.• PA46 material option allows use in high-heat applications..
Quantity Per	carton

Product Description

This mount's offset design positions bundles away from obstructions, heat or sources of abrasion. It features a low-profile head, allowing multiple tie mounts to be stacked on a single bolt and providing space savings in tight areas. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description

Offset Low-Profile M8 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA66HIRHS, Black, 3000/pkg

Global Part Name

T50ROSLPM8SMS025-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

223

Length L (Imperial)

8.9

Length L (Metric)

226.14

Offset Length(Imperial)

1.0

Offset Length(Metric)

25.5

Fixation Method

Stud Mount

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Width W (Imperial)

0.70

Width W (Metric) 17.75

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Cable Ties 157-00362

Height H (Imperial) 0.25

Height H (Metric) 6.30

Mounting Hole Diameter D (Imperial) 0.31" x 0.05

Mounting Hole Diameter D (Metric) M8 x 1.25

Stud Diameter (Metric) 8.0 mm

Stud Diameter (Imperial) 0.31

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0027
Weight (Imperial)	0.006