

Specification Sheet

Part Number: 157-00419



Low-profile head allows mounts to stack, providing more mounting versatility from a single stud

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure

Low Profile M10 Stud Mount Tie, 7.5" L, 80lb Tensile, PA66HIRHSUV, Black, 100/pkg

Article Number 157-00419

Type T80ROSLPSB10U

Color Black (BK)

Quantity Per bag

Product Description One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description Low Profile M10 Stud Mount Tie, 7.5" L, 80lb Tensile, PA66HIRHSUV, Black, 100/pkg

Global Part Name T80ROSLPSB10U-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 80.0

Minimum Tensile Strength (Metric) 335.0

Length L (Imperial) 8.5

Length L (Metric) 215.0

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.23

Width W (Metric) 5.52

Bundle Diameter Min (Imperial) 0.14

Bundle Diameter Min (Metric) 3.5

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial) 0.05

Height H (Metric)	1.35
Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	M10
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988