

Specification Sheet

Part Number: 157-00430



1-Pc Cable Tie/Stand-off Fir Tree w/Disc, 12.5mm Stand-Off, 9.1"L, 0.24-0.51", PA66HIRHSUV, Black, 100/pkg

Article Number 157-00430

Type T50ROSFTOVAL12.5SO

Color Black (BK)

Features & Benefits

- All-in-one bundling and fastening solution reduces costs and assembly time.
- Anti-rotational oval fastener forces bundle to travel in intended direction.
- Stand-off cable ties route and position bundles above a mounting hole to protect them from rubbing, heat or obstructions.

Quantity Per bag

| | |
|--|---|
| Product Description | One-piece stand-off cable tie and mount offers a simple bundling and mounting solution. The innovative design of this fir tree establishes a 360-degree interface with the panel hole, ensuring a more secure fit. The oval shape won't rotate once inserted, ensuring proper routing of wires and hoses. Stand-off feature positions bundles above a mounting hole. The disc prevents rattling in high-vibration applications and protects against debris ingress. |
| Short Description | 1-Pc Cable Tie/Stand-off Fir Tree w/Disc, 12.5mm Stand-Off, 9.1"L, 0.24-0.51", PA66HIRHSUV, Black,100/pkg |
| Global Part Name | T50ROSFTOVAL12.5SO-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 9.1 |
| Length L (Metric) | 231.3 |
| Offset Length (Imperial) | 0.49 |
| Offset Length (Metric) | 12.5 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Width W (Imperial) | 0.2 |
| Width W (Metric) | 5.1 |

| | |
|--|--|
| Bundle Diameter Min (Imperial) | 0.08 |
| Bundle Diameter Min (Metric) | 2.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.06 |
| Height H (Metric) | 1.5 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.27 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.75 |
| Mounting Hole Diameter D (Imperial) | 0.24 " x 0.48 ";0.26 " x 0.49 ";0.26 " x 0.51 ";0.28 " x 0.47 |
| Mounting Hole Diameter D (Metric) | 6.5 x 12.5 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 7.0 x 12.0 mm |
| Disc Diameter (Metric) | 17.63 x 23.63 |
| Disc Diameter (Imperial) | 0.69 " x 0.93 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |

| | |
|------------------------------------|-----------------------------------|
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)