

Specification Sheet

Part Number: 157-00431



The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole

The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt

The oval hole fir tree fits 4 common automotive oval hole sizes

The specific connector slot on this part reduces rattle and movement of clip to the wire harness connector

1-Pc Cable Tie/Offset Fir Tree w/Disc, 25mm Offset, 9.0"L, 0.24 -0.51", PA66HIRHSUV, Black, 100/pkg

Article Number	157-00431
Type	T50ROSFTOVAL25A
Color	Black (BK)
Quantity Per	bag

Product Description

This one-piece cable tie and mount offers a simple and easy-to-use method of bundling and attaching cables. The innovative fir tree design creates an interface with four different size holes that are common in the automotive industry. The fir tree's four-sided branch design enables a 360-degree interface with the panel, creating a more secure fit into the hole. The disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description	1-Pc Cable Tie/Offset Fir Tree w/Disc, 25mm Offset, 9.0"L, 0.24 -0.51", PA66HIRHSUV, Black, 100/pkg
Global Part Name	T50ROSFTOVAL25A-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	9.0
Length L (Metric)	229.3
Offset Length (Imperial)	0.98
Offset Length (Metric)	25.0
Identification Plate Position	none
Releasable Closure	No
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.05
Height H (Metric)	1.35
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 " x 0.48 ";0.26 " x 0.49 ";0.26 " x 0.51 ";0.28 " x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm 6.2 x 12.2 mm
Disc Diameter (Metric)	17.63 x 23.63
Disc Diameter (Imperial)	0.69 " x 0.93
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)

ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988