

Specification Sheet

Part Number: 157-00488



All-in-one bundling and fastening solution reduces costs and assembly time.

Variety of fir tree diameters and offset lengths address most offset applications.

High-spec materials and superior design deliver excellent performance and value.

1-Piece Cable Tie/Fir Tree Mount, M6, 25mm Offset, 9.6"L, PA66HIRHSUV, Black, 2000/ctn

Article Number	157-00488
Type	T50ROSFTM625SO
Color	Black (BK)
Quantity Per	carton

Product Description	Offset cable ties route and position bundles away from a mounting hole. Rigid offset bar eliminates potential bending of wire or cables once installed. Multiple offset distances and fir tree sizes cover the majority of industry offset applications. The tie strap's outside serration design provides a smooth surface to protect soft bundles. HellermannTyton's one-piece mounting ties offer a complete solution by both bundling and mounting. Their ideal combination of high-specification materials and superior design suit the needs of complex applications.
Short Description	1-Piece Cable Tie/Fir Tree Mount, M6, 25mm Offset, 9.6"L, PA66HIRHSUV, Black, 2000/ctn
Global Part Name	T50ROSFTM625SO-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	9.6
Length L (Metric)	244.0
Offset Length (Imperial)	0.98
Offset Length (Metric)	25.0
Fixation Method	Fir tree for round holes
Identification Plate Position	none
Releasable Closure	No
Variant	Outside Serrated

Width W (Imperial)	0.02
Width W (Metric)	5.05
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.06
Thickness T (Metric)	1.52
Height H (Imperial)	0.23
Height H (Metric)	5.8
Panel Thickness Min (Imperial)	0.197
Panel Thickness Max (Imperial)	0.197
Panel Thickness Min (Metric)	5.0
Panel Thickness Max (Metric)	5.0
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	M6 x 1

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000