

Specification Sheet

Part Number: 157-00533

One piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables.

The design of the fir tree ensures a positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes.



Disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

1-Pc Cable Tie/Fir Tree Mount w Disc, 6.4"L, 0.47 - 0.49 " Mounting Hole, PA66HS, Black, 1000/pkg

Article Number	157-00533
Type	T60SOSFT12-E
Color	Black (BK)
Quantity Per	bag

Product Description	Fir Tree Mounts offers a simple and easy to use method of bundling and mounting cables. The design of the fir tree ensures a secure and robust fit into panels with a round mounting hole between thicknesses between .03" - .28". The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. The outside serrated tie can be applied by hand and tensioned with one of HellermannTyton's manual or pneumatic hand tools.
---------------------	---

Short Description	1-Pc Cable Tie/Fir Tree Mount w Disc, 6.4"L, 0.47 - 0.49 " Mounting Hole, PA66HS, Black, 1000/pkg
Global Part Name	T60SOSFT12-E-PA66HS-BK
Minimum Tensile Strength (Imperial)	64.4
Minimum Tensile Strength (Metric)	300
Length L (Imperial)	6.4
Length L (Metric)	161.5
Fixation Method	Fir Tree for oval holes
Identification Plate Position	none
Releasable Closure	No
Variant	Outside Serrated
Width W (Imperial)	0.22
Width W (Metric)	5.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.18
Bundle Diameter Max (Metric)	30.0

Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.47 - 0.49
Mounting Hole Diameter D (Metric)	M14 x 1.5 12.0 - 12.5 mm
Mounting Hole Diameter D Min (Imperial)	0.47
Mounting Hole Diameter D Max (Imperial)	0.49
Mounting Hole Diameter D Max (Metric)	12.5
Disc Diameter (Metric)	20.0
Disc Diameter (Imperial)	0.79
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)