

## Specification Sheet

Part Number: 157-00533



One piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables.

The design of the fir tree ensures a positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes.

Disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

1-Pc Cable Tie/Fir Tree Mount w Disc, 6.4"L, 0.47 - 0.49 " Mounting Hole, PA66HS, Black, 1000/pkg

Article Number 157-00533

Type T60SOSFT12-E

Color Black (BK)

Quantity Per bag

**Product Description**  
Fir Tree Mounts offers a simple and easy to use method of bundling and mounting cables. The design of the fir tree ensures a secure and robust fit into panels with a round mounting hole between thicknesses between .03" - .28". The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. The outside serrated tie can be applied by hand and tensioned with one of HellermannTyton's manual or pneumatic hand tools.

**Short Description**  
1-Pc Cable Tie/Fir Tree Mount w Disc, 6.4"L, 0.47 - 0.49 " Mounting Hole, PA66HS, Black, 1000/pkg

Global Part Name T60SOSFT12-E-PA66HS-BK

Minimum Tensile Strength (Imperial) 64.4

Minimum Tensile Strength (Metric) 300

Length L (Imperial) 6.4

Length L (Metric) 161.5

Fixation Method Fir Tree for oval holes

Identification Plate Position none

Releasable Closure No

Variant Outside Serrated

Width W (Imperial) 0.22

Width W (Metric) 5.5

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 1.18

Bundle Diameter Max (Metric) 30.0

Panel Thickness Min (Imperial) 0.04

Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.47 - 0.49
Mounting Hole Diameter D (Metric)	12.0 - 12.5 mm M14 x 1.5
Mounting Hole Diameter D Min (Imperial)	0.47
Mounting Hole Diameter D Max (Imperial)	0.49
Mounting Hole Diameter D Max (Metric)	12.5
Disc Diameter (Metric)	20.0
Disc Diameter (Imperial)	0.79
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)