

## Specification Sheet

Part Number: 1FRP9C



Sheathing allows flexible routing and lead-out of cables  
The inner edges are beveled preventing damage to cables

Sheathing is reusable and resistant to most chemicals

Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.13" Diameter, PE-FR, Natural, 100 ft/roll

Article Number 161-05001

Type 1FRP

Color Natural (NA)

Quantity Per reel

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

Short Description Spiralwrap Protective Sheathing, 0.13" Diameter, PE-FR, Natural, 100 ft/roll

Global Part Name 1FRP-PE-FR-NA

|                                |                                       |
|--------------------------------|---------------------------------------|
| Length L (Imperial)            | 100.0                                 |
| Length L (Metric)              | 30.48                                 |
| Variant                        | Spiral Binding                        |
| Bundle Diameter Min (Imperial) | 0.06                                  |
| Bundle Diameter Min (Metric)   | 1.6                                   |
| Bundle Diameter Max (Imperial) | 0.5                                   |
| Bundle Diameter Max (Metric)   | 12.7                                  |
| Diameter D (Imperial)          | 0.125                                 |
| Diameter D (Metric)            | 3.18                                  |
| Nominal Diameter (Imperial)    | 0.13                                  |
| Nominal Diameter (Metric)      | 3.18                                  |
| Wall Thickness WT (Imperial)   | .032                                  |
| Wall Thickness WT (Metric)     | 0.81                                  |
| Material                       | Polyethylene, flame retardant (PE-FR) |
| Material Shortcut              | PE-FR                                 |

|                              |                                 |
|------------------------------|---------------------------------|
| Flammability                 | UL 94 V-2                       |
| Halogen Free                 | No                              |
| Operating Temperature        | -4°F to +176°F (-20°C to +80°C) |
| Reach Compliant (Article 33) | Yes                             |
| ROHS Compliant               | Yes                             |
| UL Recognized (US)           | Yes                             |
| Package Quantity (Imperial)  | 100                             |
| Package Quantity (Metric)    | 30.48                           |
| Customs Number               | 3926909988                      |

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)