

Specification Sheet

Part Number: 1FRP9C



Sheathing allows flexible routing and lead-out of cables
The inner edges are beveled preventing damage to cables
Sheathing is reusable and resistant to most chemicals
Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.13" Diameter, PE-FR, Natural, 100 ft/roll

| | |
|---------------------|--|
| Article Number | 161-05001 |
| Type | 1FRP |
| Color | Natural (NA) |
| Quantity Per | reel |
| Product Description | HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize. |
| Short Description | Spiralwrap Protective Sheathing, 0.13" Diameter, PE-FR, Natural, 100 ft/roll |
| Global Part Name | 1FRP-PE-FR-NA |

| | |
|--------------------------------|---------------------------------------|
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Variant | Spiral Binding |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.6 |
| Bundle Diameter Max (Imperial) | 0.5 |
| Bundle Diameter Max (Metric) | 12.7 |
| Diameter D (Imperial) | 0.125 |
| Diameter D (Metric) | 3.18 |
| Nominal Diameter (Imperial) | 0.13 |
| Nominal Diameter (Metric) | 3.18 |
| Wall Thickness WT (Imperial) | .032 |
| Wall Thickness WT (Metric) | 0.81 |
| Material | Polyethylene, flame retardant (PE-FR) |
| Material Shortcut | PE-FR |

| | |
|------------------------------|---------------------------------|
| Flammability | UL 94 V-2 |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -4°F to +176°F (-20°C to +80°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)