

## Specification Sheet

Part Number: 1NFP9C



Spiralwrap Protective Sheathing, .13" Diameter, PE, Natural, 100 ft/roll

**Article Number**

161-05013

**Type**

1NFP

**Color**

Natural (NA)

**Features & Benefits**

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

**Quantity Per**

reel

**Product Description**

HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

**Short Description**

Spiralwrap Protective Sheathing, .13" Diameter, PE, Natural, 100 ft/roll

**Global Part Name**

1NFP-PE-NA

|                                       |                   |
|---------------------------------------|-------------------|
| <b>Length L (Imperial)</b>            | 100.0             |
| <b>Length L (Metric)</b>              | 30.48             |
| <b>Variant</b>                        | Spiral Binding    |
| <b>Bundle Diameter Min (Imperial)</b> | 0.06              |
| <b>Bundle Diameter Min (Metric)</b>   | 1.6               |
| <b>Bundle Diameter Max (Imperial)</b> | 0.5               |
| <b>Bundle Diameter Max (Metric)</b>   | 12.7              |
| <b>Diameter D (imperial)</b>          | 0.125             |
| <b>Diameter D (metric)</b>            | 3.18              |
| <b>Nominal Diameter (Imperial)</b>    | 1/8               |
| <b>Nominal Diameter (Metric)</b>      | 3.18              |
| <b>Wall Thickness WT (Imperial)</b>   | 0.032             |
| <b>Wall Thickness WT (Metric)</b>     | 0.81              |
| <b>Material</b>                       | Polyethylene (PE) |
| <b>Material Shortcut</b>              | PE                |

|                                       |                                  |
|---------------------------------------|----------------------------------|
| <b>Flammability</b>                   | Flammable                        |
| <b>Halogen free</b>                   | Yes                              |
| <b>Operating Temperature (Metric)</b> | -76°F to +190°F (-60°C to +88°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                              |
| <b>ROHS Complaint</b>                 | Yes                              |
| <b>UL Recognized (US)</b>             | Yes                              |
| <b>Package Quantity(Imperial)</b>     | 100                              |
| <b>Package Quantity (Metric)</b>      | 30.48                            |
| <b>Customs Number</b>                 | 3926909988                       |