

Specification Sheet

Part Number: 2N0C



Spiralwrap Protective Sheathing, .25" Diameter, PA6, Black, 100 ft/roll

Article Number

161-05032

Type

2N

Color

Black (BK)

Features & Benefits

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

Quantity Per

reel

Product Description

HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

Short Description

Spiralwrap Protective Sheathing, .25" Diameter, PA6, Black, 100 ft/roll

Global Part Name

2N-PA6-BK

| | |
|---------------------------------------|-------------------|
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Variant | Spiral Binding |
| Bundle Diameter Min (Imperial) | 0.18 |
| Bundle Diameter Min (Metric) | 4.75 |
| Bundle Diameter Max (Imperial) | 2.0 |
| Bundle Diameter Max (Metric) | 50.8 |
| Diameter D (imperial) | 0.25 |
| Diameter D (metric) | 6.35 |
| Nominal Diameter (Imperial) | 1/4 |
| Nominal Diameter (Metric) | 6.35 |
| Wall Thickness WT (Imperial) | 0.025 |
| Wall Thickness WT (Metric) | 0.64 |
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |

| | |
|---------------------------------------|-----------------------------------|
| Flammability | Self-Extinguishing |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +250°F (-40°C to +121°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3926909987 |