

Specification Sheet

Part Number: 2N0M



Spiralwrap Protective Sheathing, .25" Diameter, PA6, Black, 1000ft/roll

Article Number

161-05033

Type

2N

Color

Black (BK)

Features & Benefits

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

Quantity Per

reel

Product Description

HellermannTyton Spiralwrap provides an effective means for routing and securing wires around corners and bends, and helps keep wires out of pinch points within moving panel doors. Spiralwrap is installed using a gapped or butted installation which impacts harnesses flexibility, wire coverage and abrasion resistance. A gapped installation leaves space between the sheathing to accommodate breakouts and adds flexibility to the harness. A butted installation wraps tightly around the bundle to provide greater abrasion resistance and add rigidity. Natural PA6 nylon material is recommended for use within enclosed environments where possibility of fire exists. Black PA6 nylon material is suitable for outdoor applications and can be used in direct sunlight for extended periods of time.

Short Description

Spiralwrap Protective Sheathing, .25" Diameter, PA6, Black, 1000ft/roll

Global Part Name

2N-PA6-BK

Length L (Imperial)

1000.0

Length L (Metric)

304.8

Variant

Spiral Binding

Bundle Diameter Min (Imperial)

0.18

Bundle Diameter Min (Metric)

4.75

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

50.8

Diameter D (imperial)

0.25

Diameter D (metric)

6.35

Nominal Diameter (Imperial)

1/4

Nominal Diameter (Metric)

6.35

Wall Thickness WT (Imperial) .025

Wall Thickness WT (Metric) 0.64

Material Polyamide 6 (PA6)

Material Shortcut PA6

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +250°F (-40°C to +121°C)

ROHS Complaint Yes

Package Quantity(Imperial) 1000.0

Package Quantity (Metric) 304.8

Customs Number 3926909988