

Specification Sheet

Part Number: 2N9M



Sheathing allows flexible routing and lead-out of cables
The inner edges are beveled preventing damage to cables

Sheathing is reusable and resistant to most chemicals

Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Natural, 1000ft/roll

Article Number	161-05035
Type	2N
Color	Natural (NA)
Quantity Per	reel

Product Description	HellermannTyton Spiralwrap provides an effective means for routing and securing wires around corners and bends, and helps keep wires out of pinch points within moving panel doors. Spiralwrap is installed using a gapped or butted installation which impacts harnesses flexibility, wire coverage and abrasion resistance. A gapped installation leaves space between the sheathing to accommodate breakouts and adds flexibility to the harness. A butted installation wraps tightly around the bundle to provide greater abrasion resistance and add rigidity. Natural PA6 nylon material is recommended for use within enclosed environments where possibility of fire exists. Black PA6 nylon material is suitable for outdoor applications and can be used in direct sunlight for extended periods of time.
Short Description	Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Natural, 1000ft/roll
Global Part Name	2N-PA6-NA
Length L (Imperial)	1000.0
Length L (Metric)	304.8
Variant	Spiral Binding
Bundle Diameter Min (Imperial)	0.18
Bundle Diameter Min (Metric)	4.75
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.8
Diameter D (Imperial)	0.25

Diameter D (Metric)	5.1
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.35
Wall Thickness WT (Imperial)	.025
Wall Thickness WT (Metric)	0.64
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Operating Temperature	-40°F to +250°F (-40°C to +121°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	1000.0
Package Quantity (Metric)	304.8
Customs Number	3926909988

