

## Specification Sheet

Part Number: 2P9C



Spiralwrap Protective Sheathing, .25" Diameter, PTFE, Natural, 100 ft/roll

<b>Article Number</b>	161-05047
<b>Type</b>	2P
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Sheathing allows flexible routing and lead-out of cables</li><li>• The inner edges are beveled preventing damage to cables</li><li>• Sheathing is reusable and resistant to most chemicals</li><li>• Spiralwrap is U.L. Recognized</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.
<b>Short Description</b>	Spiralwrap Protective Sheathing, .25" Diameter, PTFE, Natural, 100 ft/roll

**Global Part Name**

2P-PTFE-NA

**Length L (Imperial)**

100.0

**Length L (Metric)**

30.48

**Variant**

Spiral Binding

**Bundle Diameter Min (Imperial)**

0.18

**Bundle Diameter Min (Metric)**

4.75

**Bundle Diameter Max (Imperial)**

2.0

**Bundle Diameter Max (Metric)**

50.8

**Diameter D (imperial)**

0.25

**Diameter D (metric)**

6.35

**Nominal Diameter (Imperial)**

1/4

**Nominal Diameter (Metric)**

6.35

**Wall Thickness WT (Imperial)**

.030

**Wall Thickness WT (Metric)**

0.76

**Material**

Polytetrafluoroethylene (PTFE)

**Material Shortcut**

PTFE

**Flammability**

Non-Flammable

**Halogen free**

No

**Operating Temperature (Metric)**

-449°F to +500°F (-267°C to +260°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

30.48

**Customs Number**

3926909988