

## Specification Sheet

Part Number: 4P9C



Spiralwrap Protective Sheathing, 0.75" Diameter, PTFE, Natural, 100 ft/roll

**Article Number** 161-05076

**Type** 4P

**Color** Natural (NA)

**Features & Benefits**

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

**Quantity Per** reel

**Product Description** HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

<b>Short Description</b>	Spiralwrap Protective Sheathing, 0.75" Diameter, PTFE, Natural, 100 ft/roll
<b>Global Part Name</b>	4P-PTFE-NA
<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.48
<b>Variant</b>	Spiral Binding
<b>Bundle Diameter Min (Imperial)</b>	0.5
<b>Bundle Diameter Min (Metric)</b>	12.7
<b>Bundle Diameter Max (Imperial)</b>	4.0
<b>Bundle Diameter Max (Metric)</b>	102.0
<b>Diameter D (imperial)</b>	0.75
<b>Diameter D (metric)</b>	19.05
<b>Nominal Diameter (Imperial)</b>	0.75
<b>Nominal Diameter (Metric)</b>	19.05
<b>Wall Thickness WT (Imperial)</b>	.032
<b>Wall Thickness WT (Metric)</b>	0.81

<b>Material</b>	Polytetrafluoroethylene (PTFE)
<b>Material Shortcut</b>	PTFE
<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	-449°F to +500°F (-267°C to +260°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909988