

## Specification Sheet

Part Number: 5N0C



Spiralwrap Protective Sheathing, 1" Diameter, PA6, Black, 100 ft/roll

**Article Number**

161-05078

**Type**

5N

**Color**

Black (BK)

**Features & Benefits**

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

**Quantity Per**

reel

**Product Description**

HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

**Short Description**

Spiralwrap Protective Sheathing, 1" Diameter, PA6, Black, 100 ft/roll

**Global Part Name**

5N-PA6-BK

<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.48
<b>Variant</b>	Spiral Binding
<b>Bundle Diameter Min (Imperial)</b>	1.0
<b>Bundle Diameter Min (Metric)</b>	25.4
<b>Bundle Diameter Max (Imperial)</b>	7.0
<b>Bundle Diameter Max (Metric)</b>	178.0
<b>Diameter D (imperial)</b>	1.0
<b>Diameter D (metric)</b>	25.4
<b>Nominal Diameter (Imperial)</b>	1
<b>Nominal Diameter (Metric)</b>	25.4
<b>Wall Thickness WT (Imperial)</b>	0.032
<b>Wall Thickness WT (Metric)</b>	0.81
<b>Material</b>	Polyamide 6 (PA6)
<b>Material Shortcut</b>	PA6

<b>Flammability</b>	Self-Extinguishing
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +250°F (-40°C to +121°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909987