

Specification Sheet

Part Number: 5NFP9C



Spiralwrap Protective Sheathing, 1" Diameter, PE, Natural, 100 ft/roll

| | |
|--------------------------------|--|
| Article Number | 161-05080 |
| Type | 5NFP |
| Color | Natural (NA) |
| Features & Benefits | <ul style="list-style-type: none">• Sheathing allows flexible routing and lead-out of cables• The inner edges are beveled preventing damage to cables• Sheathing is reusable and resistant to most chemicals• Spiralwrap is U.L. Recognized |
| Quantity Per | reel |
| Product Description | HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize. |
| Short Description | Spiralwrap Protective Sheathing, 1" Diameter, PE, Natural, 100 ft/roll |
| Global Part Name | 5NFP-PE-NA |

| | |
|---------------------------------------|-------------------|
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Variant | Spiral Binding |
| Bundle Diameter Min (Imperial) | 1.0 |
| Bundle Diameter Min (Metric) | 25.4 |
| Bundle Diameter Max (Imperial) | 7.0 |
| Bundle Diameter Max (Metric) | 178.0 |
| Diameter D (imperial) | 1.0 |
| Diameter D (metric) | 25.4 |
| Nominal Diameter (Imperial) | 1 |
| Nominal Diameter (Metric) | 25.4 |
| Wall Thickness WT (Imperial) | 0.095 |
| Wall Thickness WT (Metric) | 2.41 |
| Material | Polyethylene (PE) |
| Material Shortcut | PE |

| | |
|---------------------------------------|----------------------------------|
| Flammability | Flammable |
| Halogen free | Yes |
| Operating Temperature (Metric) | -76°F to +190°F (-60°C to +88°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | metre |