

## Specification Sheet

Part Number: 161-05090



Sheathing allows flexible routing and lead-out of cables  
The inner edges are beveled preventing damage to cables  
Sheathing is reusable and resistant to most chemicals  
Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.38" Diameter, PE, Black, 500ft/roll

**Article Number** 161-05090

**Type** 2.5NFP0H

**Color** Black (BK)

**Quantity Per** reel

**Product Description** HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize. Polyethylene is ideal for general applications that are not affected by ordinary solvents. Ultraviolet resistant black polyethylene is for outdoor use. It has the same qualities as clear polyethylene, but also contains an ultraviolet absorber which permits it to be used in direct sunlight for long periods of time. Available in colors.

**Short Description** Spiralwrap Protective Sheathing, 0.38" Diameter, PE, Black, 500ft/roll

<b>Global Part Name</b>	2.5NFP0H-PE-BK
<b>Local Order Number 2</b>	161-05090
<b>Length L (Imperial)</b>	500.0
<b>Length L (Metric)</b>	152.4
<b>Variant</b>	Spiral Binding
<b>Bundle Diameter Min (Imperial)</b>	0.31
<b>Bundle Diameter Min (Metric)</b>	7.92
<b>Bundle Diameter Max (Imperial)</b>	3.0
<b>Bundle Diameter Max (Metric)</b>	76.2
<b>Diameter D (Imperial)</b>	0.375
<b>Diameter D (Metric)</b>	9.53
<b>Nominal Diameter (Imperial)</b>	0.38
<b>Nominal Diameter (Metric)</b>	9.53
<b>Wall Thickness WT (Imperial)</b>	.052
<b>Wall Thickness WT (Metric)</b>	1.32

<b>Material</b>	Polyethylene (PE)
<b>Material Shortcut</b>	PE
<b>Flammability</b>	Flammable
<b>Operating Temperature</b>	-76°F to +190°F (-60°C to +88°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	152.4
<b>Customs Number</b>	3926909988