

## Specification Sheet

Part Number: 161-64213



Helawrap, HWPP16, 5/8" (16mm) Dia, PP, Black, 100 ft/reel

**Article Number**

161-64213

**Type**

HWPP16

**Color**

Black (BK)

**Features & Benefits**

- Unique open design for easy branch-offs at any point along the harness.
- Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
- Flexible construction and design eliminates pinch points and minimizes bending fatigue, making it ideal for applications involving movement and vibration.
- Split shape allows for future access without disassembly.

**Quantity Per**

reel

**Product Description**

The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

|                                       |   |
|---------------------------------------|---|
| <b>Short Description</b>              | Helawrap, HWPP16, 5/8" (16mm) Dia, PP, Black, 100 ft/reel |
| <b>Global Part Name</b>               | HWPP16-PP-BK  |
| <b>Length L (Imperial)</b>            | 100.0   |
| <b>Length L (Metric)</b>              | 30.48   |
| <b>Variant</b>                        | Spiral Binding  |
| <b>Bundle Diameter Min (Imperial)</b> | 0.51  |
| <b>Bundle Diameter Min (Metric)</b>   | 12.95   |
| <b>Bundle Diameter Max (Imperial)</b> | 0.63  |
| <b>Bundle Diameter Max (Metric)</b>   | 16.0  |
| <b>Diameter D (imperial)</b>          | 0.5   |
| <b>Diameter D (metric)</b>            | 16.0  |
| <b>Nominal Diameter (Imperial)</b>    | 5/8   |
| <b>Nominal Diameter (Metric)</b>      | 16.0  |
| <b>Wall Thickness WT (Imperial)</b>   | 0.03  |
| <b>Wall Thickness WT (Metric)</b>     | 0.80  |

|  |  |
|--|--|
| <b>Material</b>                        | Polypropylene (PP)                       |
| <b>Material Shortcut</b>               | PP                                       |
| <b>Flammability</b>                    | UL 94 HB                                 |
| <b>Halogen free</b>                    | Yes                                      |
| <b>UV Resistant (Yes/No)</b>           | No                                       |
| <b>Operating Temperature (Metric)</b>  | -76°F to +230°F (-60°C to +110°C)        |
| <b>Reach Complaint(Article 33)</b>     | Yes                                      |
| <b>ROHS Complaint</b>                  | Yes                                      |
| <b>Certification/Specification WEB</b> | EDAG   ECE R 118-03 Abschnitt 6, 2017-06 |
| <b>Package Quantity(Imperial)</b>      | 100                                      |
| <b>Package Quantity (Metric)</b>       | 30.48                                    |
| <b>Customs Number</b>                  | 3926909988                               |
| <b>Weight (Metric)</b>                 | 1.16                                     |
| <b>Weight (Imperial)</b>               | 2.55                                     |

