

## Specification Sheet

Part Number: 164-11008

Highly flexible design saves space and allows bending at angles above 90 degrees, making it well suited for confined spaces.

Overlapping circular fingers eliminate need for a separate cover to retain wires and make insertion and removal of wires fast and easy.

Smooth finger edges eliminate abrasion that can damage wires.

Slotted finger pattern provides easy visibility to wires and allows heat to dissipate.



HelaDuct Flex10 Wiring Duct, 0.39" Dia., 19.7" Length, Non-Adhesive, PP, White, 100/ctn

<b>Article Number</b>	164-11008
<b>Type</b>	HelaDuct Flex10
<b>Color</b>	White (WH)
<b>Quantity Per</b>	box

**Product Description**

HelaDuct Flex provides an extremely flexible method of routing wires in restricted-space applications. Smooth, overlapping, circular finger pattern reduces wire abrasion and eliminates the need for a separate cover in order to maintain wires when installed at angles greater than 90 degrees. Quick and easy inspection, access and removal of wires reduces installation and maintenance time. Available with adhesive foam strip for temporary positioning or non-adhesive back.

<b>Short Description</b>	HelaDuct Flex10 Wiring Duct, 0.39" Dia., 19.7" Length, Non-Adhesive, PP, White, 100/ctn
<b>Global Part Name</b>	HelaDuct Flex10-PP-WH
<b>Length L (Imperial)</b>	19.7
<b>Length L (Metric)</b>	500
<b>Fixation Method</b>	Screw Mounting
<b>Width W (Imperial)</b>	0.43
<b>Width W (Metric)</b>	11.0
<b>Height H (Imperial)</b>	0.53
<b>Height H (Metric)</b>	13.5
<b>Inner Diameter D (Imperial)</b>	0.39
<b>Inner Diameter D (Metric)</b>	10
<b>Diameter D (Imperial)</b>	0.39
<b>Diameter D (Metric)</b>	10
<b>Nominal Diameter (Imperial)</b>	0.39
<b>Nominal Diameter (Metric)</b>	10

<b>Material</b>	Polypropylene (PP)
<b>Material Shortcut</b>	PP
<b>Flammability</b>	UL 94 V-0 (excluding adhesive)
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-4°F to +158°F (-20°C to +70°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100