

Specification Sheet

Part Number: 166-11810



HelaGuard Non-Metallic Conduit, Double Slit, Std Wt, 0.75" Dia, Nylon PA6, Black, 164 ft/Std. Reel

Article Number

166-11810

Type

HG-DC0750

Color

Black (BK)

Features & Benefits

- Double slit opening offers easy access during installation and maintenance.
- Material is easy to use and cut; reduces installation time and labor costs.
- Flexible, abrasion resistant and durable for a variety of applications.
- Good impact strength; recovers quickly if crushed.
- UV resistant; suitable for use in outdoor applications.
- Offered in fine or course corrugated pitch.

Product Description

A standard weight corrugated conduit with two slit openings that eases installation and maintenance of wire and cable bundles. The interlocking construction is excellent for retrofitting projects. PA6 material is highly resistant to solvents and oils, and offers UV and abrasion resistance.

Short Description

HelaGuard Non-Metallic Conduit, Double Slit, Std Wt, 0.75" Dia, Nylon PA6, Black, 164 ft/Std. Reel

Global Part Name

HG-DC0750-PA6-BK

Length L (Imperial)

164.0

Length L (Metric)

50

Inner Diameter D (Imperial)

0.81

Inner Diameter D (Metric)

20.5

Outside Diameter OD(Imperial)

1.13

Outside Diameter OD(metric)

28.5

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

28

Material

Polyamide 6 (PA6)

Material Shortcut

PA6

Flammability

Self-Extinguishing according to EN IEC 61386

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +248°F (-40°C to +120°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

164

Package Quantity (Metric)

50

Customs Number

3926909988