

Specification Sheet

Part Number: 166-90097



HelaGuard Non-Metallic IP66 45 Degree Elbow, 1.5" NPT Thread, 1.50" Dia, PA66, Black, 2/pkg

Article Number

166-90097

Type

HG150-45-1500

Color

Black (BK)

Features & Benefits

- External NPT thread provides a secure connection.
- Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to conduit and deliver a high extraction force.
- Durable nylon material has high resistance to salts, oils, weak acids and solvents.
- IP66 fitting has one-piece construction.

Quantity Per

bag

Product Description

Helaguard Non-Metallic 45-Degree Elbow Fittings provide fast fit installation, durability and extremely high pull off strength performance. Suitable for use on all types of corrugated conduits, both fine and course pitch material. Low-profile and lightweight fittings for use in OEM, automation, and control panel applications. External NPT thread pattern suitable for knockouts. Designed for easy removal with small screwdriver. IP66 ingress protection rated fittings.

Short Description

HelaGuard Non-Metallic IP66 45 Degree Elbow, 1.5" NPT Thread, 1.50" Dia, PA66, Black, 2/pkg

Global Part Name

HG150-45-1500-PA66-BK

Length L (Imperial)

4.17

Length L (Metric)

106

Variant

45° Elbow

Outside Diameter OD(Imperial)

2.99

Outside Diameter OD(metric)

76.0

Nominal Diameter (Imperial)

2-1/8

Nominal Diameter (Metric)

54

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

Flammability

UL 94 V2

Halogen free Yes

Operating Temperature (Metric) -58°F to +275°F (-50°C to +135°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 2

Package Quantity (Metric) 2

Customs Number 3926909988