

Specification Sheet

Part Number: 166-90119



HelaGuard Non-Metallic IP68 Fitting, Straight, 0.5" NPT Thread, 0.50" Dia, PA66, Black, 10/pkg

Article Number 166-90119

Type HGL050-S-0500

Color Black (BK)

Features & Benefits

- External NPT thread provides a secure connection.
- Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to conduit and deliver a high extraction force.
- Durable nylon material has high resistance to salts, oils, weak acids and solvents.
- IP68 fitting has additional conduit seal for increased protection against wind, dirt, and water.

Quantity Per bag

| | |
|--------------------------------------|--|
| Product Description | HelaGuard Non-Metallic Straight Swivel Flange fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP68 ingress protection rated fittings. |
| Short Description | HelaGuard Non-Metallic IP68 Fitting, Straight, 0.5" NPT Thread, 0.50" Dia, PA66, Black, 10/pkg |
| Global Part Name | HGL050-S-0500-PA66-BK |
| Length L (Imperial) | 1.73 |
| Length L (Metric) | 44 |
| Variant | Straight |
| Outside Diameter OD(Imperial) | 1.26 |
| Outside Diameter OD(metric) | 32.0 |
| Nominal Diameter (Imperial) | 1/2 |
| Nominal Diameter (Metric) | 21 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |

| | |
|---------------------------------------|-----------------------------------|
| Halogen free | Yes |
| Operating Temperature (Metric) | -58°F to +275°F (-50°C to +135°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| UL Listed (US and Canada) | Yes |
| UL Listed (US | Yes |
| Package Quantity(Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 3926909988 |