

## Specification Sheet

Part Number: 166-90137



HelaGuard Non-Metallic IP65 Fitting, Straight, NPT Thread, 1.25" Dia, PA66, Black, 2/pkg

**Article Number** 166-90137

**Type** PSR125-S-1250

**Color** Black (BK)

### Features & Benefits

- External NPT thread provides a secure connection.
- Twist-on installation makes future access fast and easy.
- Internal spigot design helps ease threading of fitting onto conduit.
- All-around “teeth” attach firmly to conduit and deliver a high extraction force.
- Durable nylon material has high resistance to salts, oils, weak acids and solvents.
- IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

**Quantity Per** bag

<b>Product Description</b>	Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.
<b>Short Description</b>	HelaGuard Non-Metallic IP65 Fitting, Straight, NPT Thread, 1.25" Dia, PA66, Black, 2/pkg
<b>Global Part Name</b>	PSR125-S-1250-PA66-BK
<b>Length L (Imperial)</b>	2.32
<b>Length L (Metric)</b>	59
<b>Variant</b>	Straight
<b>Outside Diameter OD(Imperial)</b>	2.36
<b>Outside Diameter OD(metric)</b>	60
<b>Nominal Diameter (Imperial)</b>	1.25
<b>Nominal Diameter (Metric)</b>	40
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2

<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +248°F (-40°C to +120°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	2
<b>Package Quantity (Metric)</b>	2
<b>Customs Number</b>	3926909988