

## Specification Sheet

Part Number: 166-90203

Flame retardant material; meets low flammability, smoke and toxicity ratings.

Easy to use and cut; reduces installation time and labor costs.

Flexible, abrasion resistant and durable for a variety of applications.

Good impact strength; recovers quickly if crushed.

Rated UL94 V0.

UV resistant; suitable for use in outdoor applications.

Offered in fine or course corrugated pitch.



HelaGuard Non-Metallic Conduit, Flame Retardant, Std Wt, 0.50" Dia, PA6-FR, Bk, 100 ft/Std. Reel

**Article Number** 166-90203

**Type** HG-FR0500

**Color** Black (BK)

**Quantity Per** reel

**Product Description** A standard weight corrugated conduit made of a flame retardant material for use in applications in which high fire protection and low flammability are primary requirements. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard Non-Metallic Fittings for IP66 rating or greater protection against water, wind and dirt.

<b>Short Description</b>	HelaGuard Non-Metallic Conduit, Flame Retardant, Std Wt, 0.50" Dia, PA6-FR, Bk, 100 ft/Std. Reel
<b>Global Part Name</b>	HG-FR0500-PA6FR-BK
<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.5
<b>Inner Diameter D (Imperial)</b>	0.66
<b>Inner Diameter D (Metric)</b>	16.7
<b>Outside Diameter OD (Imperial)</b>	0.84
<b>Outside Diameter OD (Metric)</b>	21.2
<b>Nominal Diameter (Imperial)</b>	0.5
<b>Nominal Diameter (Metric)</b>	21
<b>Material</b>	Polyamide 6, flame retardant (PA6FR)
<b>Material Shortcut</b>	PA6FR
<b>Flammability</b>	UL 94 V0 Limited Fire Hazard Low generation of toxic gases and corrosive acid Halogen-Free Low Smoke Generation
<b>Halogen Free</b>	Yes

<b>Operating Temperature</b>	-40°F to +248°F (-40°C to +120°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	ASTM 1354 Exova   NFPA130: 2017 ASTM E 162 ASTM E 662
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.5
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)