

Specification Sheet

Part Number: 166-90203



HelaGuard Non-Metallic Conduit, Flame Retardant, Std Wt, 0.50" Dia, PA6-FR, Bk, 100 ft/Std. Reel

Article Number 166-90203

Type HG-FR0500

Color Black (BK)

Features & Benefits

- Flame retardant material; meets low flammability, smoke and toxicity ratings.
- Easy to use and cut; reduces installation time and labor costs.
- Flexible, abrasion resistant and durable for a variety of applications.
- Good impact strength; recovers quickly if crushed.
- Rated UL94 V0.
- UV resistant; suitable for use in outdoor applications.
- Offered in fine or course corrugated pitch.

Quantity Per reel

Product Description	A standard weight corrugated conduit made of a flame retardant material for use in applications in which high fire protection and low flammability are primary requirements. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard Non-Metallic Fittings for IP66 rating or greater protection against water, wind and dirt.
Short Description	HelaGuard Non-Metallic Conduit, Flame Retardant, Std Wt, 0.50" Dia, PA6-FR, Bk, 100 ft/Std. Reel
Global Part Name	HG-FR0500-PA6FR-BK
Length L (Imperial)	100.0
Length L (Metric)	30.5
Inner Diameter D (Imperial)	0.66
Inner Diameter D (Metric)	16.7
Outside Diameter OD(Imperial)	0.84
Outside Diameter OD(metric)	21.2
Nominal Diameter (Imperial)	1/2
Nominal Diameter (Metric)	21
Material	Polyamide 6, flame retardant (PA6FR)

Material Shortcut	PA6FR
Flammability	Limited Fire Hazard Low generation of toxic gases and corrosive acid Low Smoke Generation Halogen-Free UL 94 V0
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +248°F (-40°C to +120°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.5
Customs Number	3926909988