

Specification Sheet

Part Number: 166-90212

Very high impact strength; recovers completely if crushed and provides excellent fatigue life.

Highly UV resistant; suitable for use in outdoor applications.

Offered in fine or course corrugated pitch.

Offered with or without slit; slit options offer easy access during installation and maintenance.



HelaGuard Non-Metallic Conduit, Std. Weight, 1.25" Dia, Nylon PA12, Black, 50 ft/Std. Reel

Article Number 166-90212

Type HG-HI1250

Color Black (BK)

Quantity Per reel

Product Description A standard weight corrugated conduit made of PA12 nylon that offers superior impact resistance, making it ideal for protecting wire and cable bundles in conditions with continual movement or bending. This material is highly resistant to UV light, solvents and oils. Combine with HelaGuard Non-Metallic Fittings to achieve IP66 or greater protection against water, wind and dirt.

Short Description	HelaGuard Non-Metallic Conduit, Std. Weight, 1.25" Dia, Nylon PA12, Black, 50 ft/Std. Reel
Global Part Name	HG-HI1250-PA12-BK
Length L (Imperial)	50.0
Length L (Metric)	15.2
Inner Diameter D (Imperial)	1.40
Inner Diameter D (Metric)	35.5
Outside Diameter OD (Imperial)	1.68
Outside Diameter OD (Metric)	42.5
Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	42
Material	Polyamide 12 (PA12)
Material Shortcut	PA12
Flammability	Self-Extinguishing according to EN IEC 61386
Halogen Free	Yes

Operating Temperature -58°F to +230°F (-50°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 15.2

Customs Number 3926909988