

## Specification Sheet

Part Number: 166-90230



HelaGuard Non-Metallic IP66 Conduit Coupler, 0.38" to 0.38" Dia, PA66, Black, 10/pkg

**Article Number** 166-90230

**Type** HG038-HG038

**Color** Black (BK)

**Features & Benefits**

- One-piece fitting used to join conduits of same diameters.
- Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to conduit and deliver a high extraction force.
- Durable nylon material has high resistance to salts, oils, weak acids and solvents.
- IP66 ingress protection rating against water, dust and wind.

**Quantity Per** bag

<b>Product Description</b>	HelaGuard Non-Metallic Conduit Coupler is used to join two same diameter corrugated conduits together. Couplers feature a snap-on design for a quick, secure connection. Designed for easy removal with a small screwdriver. Suitable for use on all types of corrugated conduits, both fine and course pitch material. IP66 ingress protection rated fittings.
<b>Short Description</b>	HelaGuard Non-Metallic IP66 Conduit Coupler, 0.38" to 0.38" Dia, PA66, Black, 10/pkg
<b>Global Part Name</b>	HG038-HG038-PA66-BK
<b>Length L (Imperial)</b>	2.32
<b>Length L (Metric)</b>	59
<b>Variant</b>	Coupler
<b>Outside Diameter OD(Imperial)</b>	1.14
<b>Outside Diameter OD(metric)</b>	29
<b>Nominal Diameter (Imperial)</b>	3/8
<b>Nominal Diameter (Metric)</b>	16
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66

<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-58°F to +275°F (-50°C to +135°C)
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	10
<b>Package Quantity (Metric)</b>	10