

Specification Sheet

Part Number: 166-90230



HelaGuard Non-Metallic IP66 Conduit Coupler, 0.38" to 0.38" Dia, PA66, Black, 10/pkg

Article Number	166-90230
Type	HG038-HG038
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• One-piece fitting used to join conduits of same diameters.• Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.• All-around "teeth" attach firmly to conduit and deliver a high extraction force.• Durable nylon material has high resistance to salts, oils, weak acids and solvents.• IP66 ingress protection rating against water, dust and wind.
Quantity Per	bag

Product Description

HelaGuard Non-Metallic Conduit Coupler is used to join two same diameter corrugated conduits together. Couplers feature a snap-on design for a quick, secure connection. Designed for easy removal with a small screwdriver. Suitable for use on all types of corrugated conduits, both fine and course pitch material. IP66 ingress protection rated fittings.

Short Description

HelaGuard Non-Metallic IP66 Conduit Coupler, 0.38" to 0.38" Dia, PA66, Black, 10/pkg

Global Part Name

HG038-HG038-PA66-BK

Length L (Imperial)

2.32

Length L (Metric)

59

Variant

Coupler

Outside Diameter OD(Imperial)

1.14

Outside Diameter OD(metric)

29

Nominal Diameter (Imperial)

3/8

Nominal Diameter (Metric)

16

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-58°F to +275°F (-50°C to +135°C)

ROHS Complaint

Yes

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

10

Package Quantity (Metric)

10