

Specification Sheet

Part Number: 166-90230



HelaGuard Non-Metallic Fitting, Conduit Coupler, IP66, 0.38" to 0.38" Dia, PA66, Black, 10/pkg

Article Number	166-90230
Type	HG038-HG038
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• One-piece fitting used to join conduits of same diameters.• Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.• All-around "teeth" attach firmly to conduit and deliver a high extraction force.• Durable nylon material has high resistance to salts, oils, weak acids and solvents.• IP66 ingress protection rating against water, dust and wind.
Quantity Per	bag

Product Description

Used to join two same diameter corrugated conduits together, couplers feature a snap-on design for a quick, secure connection. Designed for easy removal with a small screwdriver. Suitable for use on all types of corrugated conduits, both fine and course pitch material.

Short Description	HelaGuard Non-Metallic Fitting, Conduit Coupler, IP66, 0.38" to 0.38" Dia, PA66, Black, 10/pkg
Global Part Name	HG038-HG038-PA66-BK
Length L (Imperial)	2.32
Length L (Metric)	59
Variant	Coupler
Outside Diameter OD(Imperial)	1.14
Outside Diameter OD(metric)	29
Nominal Diameter (Imperial)	3/8
Nominal Diameter (Metric)	16
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
ROHS Complaint	Yes

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

10

Package Quantity (Metric)

10