

## Specification Sheet

Part Number: 166-90247



HelaGuard SR PVC Tubing, Smooth Bore, Smooth Cover, Std Wt, 0.38" Dia, Bk, 100 ft/Std. Reel

Article Number	166-90247
Type	LPC0380
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Spiral reinforced construction provides protection from crushing yet remains extremely flexible.</li><li>• Lightweight, easy-to-use material reduces installation time and labor costs.</li><li>• Material stands up to vibration and limited torsional movement without creation of stress points or cracks.</li><li>• Smooth inside bore protects wires and eases insertion of wire bundles.</li><li>• UV resistant; suitable for use in outdoor applications.</li><li>• Outer surface wipes clean in wash-down environments.</li></ul>
Quantity Per	reel

### Product Description

A lightweight, smooth tubing made of a spiral reinforced PVC material that provides high flexibility; well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Metallic or Non Metallic Compression (PSR) Fittings for IP67 rating.

<b>Short Description</b>	HelaGuard SR PVC Tubing, Smooth Bore, Smooth Cover, Std Wt, 0.38" Dia, Bk, 100 ft/Std. Reel
<b>Global Part Name</b>	LPC0380-PVC-BK
<b>Length L (Imperial)</b>	100.0
<b>Length L (Metric)</b>	30.5
<b>Inner Diameter D (Imperial)</b>	0.47
<b>Inner Diameter D (Metric)</b>	12
<b>Outside Diameter OD(Imperial)</b>	0.70
<b>Outside Diameter OD(metric)</b>	17.8
<b>Nominal Diameter (Imperial)</b>	3/8
<b>Nominal Diameter (Metric)</b>	16
<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC
<b>Flammability</b>	Self-Extinguishing according to EN IEC 61386-1
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	+23°F to +158°F (-5°C to +70°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

30.5

**Customs Number**

3926909987