

Specification Sheet

Part Number: 166-90251



HelaGuard SR PVC Tubing, Smooth Bore, Smooth Cover, Std Wt, 1.25" Dia, Bk, 100 ft/Std. Reel

Article Number 166-90251

Type LPC1250

Color Black (BK)

Features & Benefits

- Spiral reinforced construction provides protection from crushing yet remains extremely flexible.
- Lightweight, easy-to-use material reduces installation time and labor costs.
- Material stands up to vibration and limited torsional movement without creation of stress points or cracks.
- Smooth inside bore protects wires and eases insertion of wire bundles.
- UV resistant; suitable for use in outdoor applications.
- Outer surface wipes clean in wash-down environments.

Quantity Per reel

Product Description	A lightweight, smooth tubing made of a spiral reinforced PVC material that provides high flexibility; well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Metallic or Non Metallic Compression (PSR) Fittings for IP67 rating.
Short Description	HelaGuard SR PVC Tubing, Smooth Bore, Smooth Cover, Std Wt, 1.25" Dia, Bk, 100 ft/Std. Reel
Global Part Name	LPC1250-PVC-BK
Length L (Imperial)	100.0
Length L (Metric)	30.5
Inner Diameter D (Imperial)	1.39
Inner Diameter D (Metric)	35.4
Outside Diameter OD(Imperial)	1.65
Outside Diameter OD(metric)	41.8
Nominal Diameter (Imperial)	1-1/4
Nominal Diameter (Metric)	40
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Flammability	Self-Extinguishing according to EN IEC 61386-1
Halogen free	No
Operating Temperature (Metric)	+23°F to +158°F (-5°C to +70°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.5
Customs Number	3926909988