

Specification Sheet

Part Number: 166-90280



HelaGuard Non-Metallic Conduit, Std. Weight, 1.25" Dia, Nylon PA6, Gray, 50 ft/reel

Article Number	166-90280
Type	HG-SW1258
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">•Material is easy to use and cut; reduces installation time and labor costs.•Flexible, abrasion resistant and durable for a variety of applications.•Good impact strength; recovers quickly if crushed.•UV resistant; suitable for use in outdoor applications.•Offered in fine or coarse corrugated pitch.
Quantity Per	reel

Product Description

A standard-weight corrugated conduit made of PA6 nylon that offers flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection against water, wind and dirt.

Short Description

HelaGuard Non-Metallic Conduit, Std. Weight, 1.25" Dia, Nylon PA6, Gray, 50 ft/reel

Global Part Name

HG-SW1258-PA6-GY

Length L (Imperial)

50.0

Length L (Metric)

15.2

Outside Diameter OD(Imperial)

1.67

Outside Diameter OD(metric)

42.5

Nominal Diameter (Imperial)

1-1/4

Nominal Diameter (Metric)

42

Material

Polyamide 6 (PA6)

Material Shortcut

PA6

Flammability

Self-Extinguishing according to EN IEC 61386-1

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +248°F (-40°C to +120°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

UL Listed (US and Canada)

Yes

UL Listed (US)

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

15.2