

Specification Sheet

Part Number: 166-90332



HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 1/2" NPT Thread, 0.38" Dia, PA66, Black, 10/pkg

| | |
|---------------------|--|
| Article Number | 166-90332 |
| Type | HG038-90-0500 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• External NPT thread provides a secure connection.• Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.• Elbow features a smooth, swept bore to ease cable installation.• All-around "teeth" attach firmly to conduit and deliver a high extraction force.• Durable nylon material has high resistance to salts, oils, weak acids and solvents.• IP66 fitting has one-piece construction. |
| Quantity Per | bag |

Product Description

HelaGuard Non-Metallic 90-Degree Elbow fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

| | |
|---------------------------------------|--|
| Short Description | HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 1/2" NPT Thread, 0.38" Dia, PA66, Black, 10/pkg |
| Global Part Name | HG038-90-0500-PA66-BK |
| Length L (Imperial) | 2.01 |
| Length L (Metric) | 51 |
| Variant | 90° Elbow |
| Outside Diameter OD(Imperial) | 1.14 |
| Outside Diameter OD(metric) | 29 |
| Nominal Diameter (Imperial) | 3/8 |
| Nominal Diameter (Metric) | 16 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -58°F to +275°F (-50°C to +135°C) |
| Reach Complaint(Article 33) | Yes |

| | |
|--------------------------------------|------------|
| ROHS Complaint | Yes |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 3926909988 |