

Specification Sheet

Part Number: 166-90453

Material is easy to use and cut; reduces installation time and labor costs. Flexible, abrasion resistant and durable for a variety of applications.

Good impact strength; recovers quickly if crushed.

UV resistant; suitable for use in outdoor applications.

Offered in fine or coarse corrugated pitch.

Offered with or without slit; slit options offer easy access during installation and maintenance.



HelaGuard Non-Metallic Conduit, Light Weight, 0.25" Dia, Nylon PA6 Slit, Black, 200 ft/Std. Reel

Article Number	166-90453
Type	HG-SWSL0250
Color	Black (BK)
Quantity Per	reel

Product Description A standard weight corrugated conduit made of PA6 nylon that offers flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection against water, wind and dirt.

Short Description	HelaGuard Non-Metallic Conduit, Light Weight, 0.25" Dia, Nylon PA6 Slit, Black, 200 ft/Std. Reel
Global Part Name	HG-SWSL0250-PA6-BK
Length L (Imperial)	200.0
Length L (Metric)	61.0
Outside Diameter OD (Imperial)	0.39
Outside Diameter OD (Metric)	10.0
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	10
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	Self-extinguishing according to EN IEC 61386
Halogen Free	Yes
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 61.0

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)