


Specification Sheet

Part Number: FSU25-M25-C-S



Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Two part swivel fitting comprised of shell, body and elastomer seal delivers IP65 ingress protection.

External thread swivels about main body even after tightening.

Metallic Compression Fitting, Straight Swivel, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Article Number	166-90510
Type	FSU25-M25-C-S
Color	Metal (ML)
Quantity Per	pack
Product Description	Two-part nickel plated brass straight fitting with swivel external metric thread. Fitting comprised of shell and body suitable for knockout or threaded metric entries. For use with FSU, FPU, and LFHU flexible metal conduit.
Short Description	Metallic Compression Fitting, Straight Swivel, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg
Global Part Name	FSU25-M25-C-S-NPB-ML

Technical Description Manufacturer Reference Number: FSU25-M25-C-S

Length L (Imperial) 2.00

Length L (Metric) 50.7

Variant Straight

Height H (Imperial) 1.38

Height H (Metric) 35.0

Nominal Diameter (Imperial) 0.75

Nominal Diameter (Metric) 25.0

Material Nickel Plated Brass (NPB)

Material Shortcut NPB

Halogen Free Yes

Operating Temperature -58°F to +275°F (-50°C to +135°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10