

Specification Sheet

Part Number: FSU25-M25-C90



Metallic Compression Fitting, 90-Elbow, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Article Number	166-90515
Type	FSU25-M25-C90
Color	Metal (ML)
Features & Benefits	<ul style="list-style-type: none">• Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.• Fitting includes elastomeric sealing washer for IP65 ingress protection.• Suitable for knockouts or Metric threaded entries.
Quantity Per	pack

Product Description

Multi-part 90 degree elbow compression fitting with fixed external metric thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.

Short Description	Metallic Compression Fitting, 90-Elbow, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg
Global Part Name	FSU25-M25-C90-NPB/PA6-ML
Technical Description	Manufacturer Reference Number: FSU25-M25-C90
Length L (Imperial)	1.93
Length L (Metric)	49.0
Variant	90° Elbow
Height H (Imperial)	1.38
Height H (Metric)	35.0
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	25.0
Material	Nickel Plated Brass (NPB) Polyamide 6 (PA6)
Material Shortcut	NPB PA6
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Reach Complaint(Article 33)	Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

10

Package Quantity (Metric)

10