

Specification Sheet

Part Number: FSU25-M25-C90



Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Fitting includes elastomeric sealing washer for IP65 ingress protection.

Suitable for knockouts or Metric threaded entries.

Metallic Compression Fitting, 90-Elbow, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Article Number 166-90515

Type FSU25-M25-C90

Color Metal (ML)

Quantity Per pack

Product Description Multi-part 90 degree elbow compression fitting with fixed external metric thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.

Short Description Metallic Compression Fitting, 90-Elbow, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Global Part Name	FSU25-M25-C90-NPB/PA6-ML
Technical Description	Manufacturer Reference Number: FSU25-M25-C90
Length L (Imperial)	1.93
Length L (Metric)	49.0
Variant	90° Elbow
Height H (Imperial)	1.38
Height H (Metric)	35.0
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	25.0
Material	Polyamide 6 (PA6) Nickel Plated Brass (NPB)
Material Shortcut	PA6 NPB
Halogen Free	Yes
Operating Temperature	-58°F to +275°F (-50°C to +135°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)