

## Specification Sheet

Part Number: FSU40-M40-C



Metallic Compression Fitting, Straight, M40 Metric Thread, 1.25" (40mm) Dia, NPB Metal, 1/pkg

Article Number

166-90543

Type

FSU40-M40-C

Color

Metal (ML)

### Features & Benefits

- Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.
- Fitting includes elastomeric sealing washer for IP65 ingress protection.
- Suitable for knockouts or NPT / Metric threaded entries as fitting rotates until tightened.

Quantity Per

pack

### Product Description

Multipart straight compression fitting with fixed external thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.

<b>Short Description</b>	Metallic Compression Fitting, Straight, M40 Metric Thread, 1.25" (40mm) Dia, NPB Metal, 1/pkg
<b>Global Part Name</b>	FSU40-M40-C-NPB/PA6-ML
<b>Technical Description</b>	Manufacturer Reference Number: FSU40-M40-C
<b>Length L (Imperial)</b>	1.87
<b>Length L (Metric)</b>	47.5
<b>Variant</b>	Straight
<b>Height H (Imperial)</b>	1.24
<b>Height H (Metric)</b>	56.0
<b>Nominal Diameter (Imperial)</b>	1-1/4
<b>Nominal Diameter (Metric)</b>	40.0
<b>Material</b>	Polyamide 6 (PA6) Nickel Plated Brass (NPB)
<b>Material Shortcut</b>	PA6 NPB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-58°F to +275°F (-50°C to +135°C)
<b>Reach Complaint(Article 33)</b>	Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

1

**Package Quantity (Metric)**

1