

Specification Sheet

Part Number: FSU40-M40-C



Metallic Compression Fitting, Straight, M40 Metric Thread, 1.25" (40mm) Dia, NPB Metal, 1/pkg

Article Number 166-90543

Type FSU40-M40-C

Color Metal (ML)

Features & Benefits

- Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.
- Fitting includes elastomeric sealing washer for IP65 ingress protection.
- Suitable for knockouts or NPT / Metric threaded entries as fitting rotates until tightened.

Quantity Per pack

Product Description	Multipart straight compression fitting with fixed external thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.
Short Description	Metallic Compression Fitting, Straight, M40 Metric Thread, 1.25" (40mm) Dia, NPB Metal, 1/pkg
Global Part Name	FSU40-M40-C-NPB/PA6-ML
Technical Description	Manufacturer Reference Number: FSU40-M40-C
Length L (Imperial)	1.87
Length L (Metric)	47.5
Variant	Straight
Height H (Imperial)	1.24
Height H (Metric)	56.0
Nominal Diameter (Imperial)	1-1/4
Nominal Diameter (Metric)	40.0
Material	Polyamide 6 (PA6) Nickel Plated Brass (NPB)

Material Shortcut	PA6 NPB
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1
Package Quantity (Metric)	1