


Specification Sheet

Part Number: FSU50-M50-C

Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Fitting includes elastomeric sealing washer for IP65 ingress protection.

Suitable for knockouts or NPT / Metric threaded entries as fitting rotates until tightened.



Metallic Compression Fitting, Straight, M50 Metric Thread, 1.5" (50mm) Dia, NPB Metal, 1/pkg

Article Number

166-90544

Type

FSU50-M50-C

Color

Metal (ML)

Quantity Per

pack

Product Description

Multipart straight compression fitting with fixed external thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.

Short Description

Metallic Compression Fitting, Straight, M50 Metric Thread, 1.5" (50mm) Dia, NPB Metal, 1/pkg

Global Part Name	FSU50-M50-C-NPB/PA6-ML
Technical Description	Manufacturer Reference Number: FSU50-M50-C
Length L (Imperial)	2.01
Length L (Metric)	51.0
Variant	Straight
Height H (Imperial)	1.38
Height H (Metric)	70.0
Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	50.0
Material	Nickel Plated Brass (NPB) Polyamide 6 (PA6)
Material Shortcut	PA6 NPB
Halogen Free	Yes
Operating Temperature	-58°F to +275°F (-50°C to +135°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)