

## Specification Sheet

Part Number: FSU20-M20-M



Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP54 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M20 Metric Thread, 1/2" (20mm) Dia, NPB Metal, 10/pkg

<b>Article Number</b>	166-90549
<b>Type</b>	FSU20-M20-M
<b>Color</b>	Metal (ML)
<b>Quantity Per</b>	pack
<b>Product Description</b>	Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FSU, FPU and LFHU flexible metal conduit.
<b>Short Description</b>	Metallic Compression Fitting, Fixed Straight, M20 Metric Thread, 1/2" (20mm) Dia, NPB Metal, 10/pkg
<b>Global Part Name</b>	FSU20-M20-M-NPB-ML

**Technical Description** Manufacturer Reference Number: FSU20-M20-M

**Length L (Imperial)** 1.03

**Length L (Metric)** 26.3

**Variant** Straight

**Height H (Imperial)** 0.94

**Height H (Metric)** 24.0

**Nominal Diameter (Imperial)** 0.5

**Nominal Diameter (Metric)** 20.0

**Material** Nickel Plated Brass (NPB)

**Material Shortcut** NPB

**Halogen Free** Yes

**Operating Temperature** -58°F to +572°F (-50°C to +300°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 10

**Package Quantity (Metric)** 10