

Specification Sheet

Part Number: FSU25-M25-M



Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP54 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Article Number 166-90550

Type FSU25-M25-M

Color Metal (ML)

Quantity Per pack

Product Description Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FSU, FPU and LFHU flexible metal conduit.

Short Description Metallic Compression Fitting, Fixed Straight, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Global Part Name FSU25-M25-M-NPB-ML

Technical Description

Manufacturer Reference Number: FSU25-M25-M

Length L (Imperial)

1.14

Length L (Metric)

32.5

Variant

Straight

Height H (Imperial)

1.14

Height H (Metric)

29.0

Nominal Diameter (Imperial)

0.75

Nominal Diameter (Metric)

25.0

Material

Nickel Plated Brass (NPB)

Material Shortcut

NPB

Halogen Free

Yes

Operating Temperature

-58°F to +572°F (-50°C to +300°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10