

Specification Sheet

Part Number: FSU32-M32-M



Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP54 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M32 Metric Thread, 1" (32mm) Dia, NPB Metal, 2/pkg

Article Number	166-90551
Type	FSU32-M32-M
Color	Metal (ML)
Quantity Per	pack
Product Description	Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FSU, FPU and LFHU flexible metal conduit.
Short Description	Metallic Compression Fitting, Fixed Straight, M32 Metric Thread, 1" (32mm) Dia, NPB Metal, 2/pkg
Global Part Name	FSU32-M32-M-NPB-ML

Technical Description

Manufacturer Reference Number: FSU32-M32-M

Length L (Imperial)

1.45

Length L (Metric)

36.8

Variant

Straight

Height H (Imperial)

1.42

Height H (Metric)

36.0

Nominal Diameter (Imperial)

1

Nominal Diameter (Metric)

32.0

Material

Nickel Plated Brass (NPB)

Material Shortcut

NPB

Halogen Free

Yes

Operating Temperature

-58°F to +572°F (-50°C to +300°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Package Quantity (Imperial) 2

Package Quantity (Metric) 2