

Specification Sheet

Part Number: B-M20-M25-EXD



Hazardous Area Metallic Thread Converter, M20 External/M25 Internal Thread, NPB Metal, 1/pkg

Article Number 166-90631

Type B-M20-M25-EXD

Color Metal (ML)

Features & Benefits

- Quickly converts thread size or style for use in threaded entries.
- Obtain IP68 level ingress protection with use of sealing washer.
- Suitable for use in Zone 1, Zone 2, Zone 21 and Zone 22 hazardous areas.
- ATEX and IECEx EX d (Flameproof).
- ATEX and IECEx EX e (Increased Safety).
- ATEX and IECEx EX t (Dust Ignition Protection).

Quantity Per pack

Product Description	Nickel plated brass thread converters used to increase, reduce or convert thread types in hazardous environments. For use with Flexicon's LTP-EXD fittings. Achieves IP68 level ingress protection with use of sealing washer.
Short Description	Hazardous Area Metallic Thread Converter, M20 External/M25 Internal Thread, NPB Metal, 1/pkg
Global Part Name	B-M20-M25-EXD-NPB-SR
Technical Description	Manufacturer Reference Number: B-M20-M25-EXD
Variant	Converter
Height H (Imperial)	0.89
Height H (Metric)	22.5
Nominal Diameter (Metric)	25
Material	Nickel Plated Brass (NPB)
Material Shortcut	NPB
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Use Conditions	For Indoor Use Only

Package Quantity(Imperial) 1

Package Quantity (Metric) 1